



► Performance

- water depth range: 0.5 – 100 m
- penetration: up to 20 m, depending on sediments
- layer resolution: up to 7.5 cm
- motion compensation: heave
- beam width @ 3dB: $\pm 2.5^\circ$ / footprint < 9% of water depth for both frequencies

► Transmitter

- primary frequencies: approx. 100 kHz (band 90 – 110 kHz)
- secondary low frequency: 10 kHz (band 5 – 15 kHz)
- primary source level: > 236 dB// μ Pa re 1 m
- pulse width: 100 – 500 μ s
- pulse rate: up to 40/s
- pulse type: CW, Ricker

► Acquisition

- primary frequency: 100 kHz (echo sounder, bottom track)
- secondary low frequency: 10 kHz (full-waveform sub-bottom data)
- sample rate 70 kHz @ 24 bit

► System Components

- transceiver unit 1/2 19 inch / 4 U (WHD: 0.30 m x 0.21 m x 0.40 m; 13 kg)
- transducer incl. 15 m cable (WHD: 0.30 m x 0.09 m x 0.22 m; 13 kg)
- system control: external PC / Notebook / Tablet via Ethernet / WiFi

SES-2000 smart Parametric Sub-bottom Profiler

► Software

- SESWIN data acquisition software
- SES Convert SEG-Y/XTF data export
- SES NetView remote display
- ISE post-processing software (option)

► Power Supply Requirements

- 100 – 240 V AC / 50 – 60 Hz
- or 12 V DC or 24 V DC (option)
- power consumption: < 100 W

Innomar Technologie GmbH
Schutower Ringstraße 4 | D-18069 Rostock
Phone (Fax) +49 381 44079-0 (-299)
E-Mail info@innomar.com



www.innomar.com